

About Us



1968

established since



293 M€

2023 revenue



80

countries



70 million m²

of Reinforced Earth®
walls



+100.000

structures around
the world



102,8 m

tallest structure


As global specialist we operate as **designer** and **supplier** of civil engineering solutions that **Retain, Cross, Protect and Strengthen**. As the **inventor of the Reinforced Earth® solution**, our strength is the result of an **unrivalled combination of expertise with over 60 years of experience** in the fields of **soil-structure interaction** and **engineered backfills**.

Geoquest delivers **its leading technologies** to serve clients' projects, from the simplest to the most extraordinary. Guided by our focus on **innovation** and our **culture of excellence in client care**, we offer **durable solutions**. We build on our **global expertise**, which is applied by our **local companies** to develop new applications to address challenges and ensure sustainability of our solutions.

Watch our Retain, Cross,
Protect, Strengthen video.



Engineering expertise, innovation and
excellence in client care to deliver
sustainable solutions.



To contact us and learn more about Geoquest products and services
please visit geoquest.ca/contact

Geoquest | 5090 Explorer Drive, Suite 400, Mississauga, ON L4W 4T9 | Tel: +1 (905) 564-0896

©2025 Soletanche Freyssinet – The text, photos and other information contained in this catalogue are the property of the Soletanche Freyssinet Group.
Any reproduction, display or other use without the prior consent of Soletanche Freyssinet is prohibited.
Soletanche Freyssinet promotes the use of paper pulp from sustainably managed forests. If provided in print format by Geoquest, the paper used in this catalogue is certified in accordance with the stringent rules of the PEFC (Program for the Endorsement of Forest Certification).
Publication: January 2025



TerraLink®
THE SHORED REINFORCED EARTH® WALL SYSTEM



TerraLink®

The shored Reinforced Earth® wall system

The TerraLink® technique allows the construction of Reinforced Earth® walls in front of existing structures, with narrow space between them. Since the reinforced fill zone is not wide enough to accommodate conventional lengths of reinforcements, the acceptable solution consists in connecting the Reinforced Earth® mass to the existing structure. The whole configuration, called TerraLink®, forms **a shored retaining wall** that ensures a sound structural behavior.

TerraLink® elements are similar to those used for Reinforced Earth® solution: soil reinforcements (steel or geosynthetic), connected to modular facing systems (precast concrete panels, welded wire mesh and connection parts). These elements are placed between well compacted backfill layers. The main feature is that reinforcements are linked to the rear part (backface) of the system through the existing structure, which enables combination or continuity of the reinforcements between the narrow Reinforced Earth® wall and the existing structure.



Friction Link system with synthetic strips



Direct Link system with synthetic strips

Two types of linked system are possible

The choice of the appropriate system depends on several factors: geometrical site configuration, type of existing structures, and type of reinforcements among other considerations.

Friction Link system

Additional reinforcements are inserted between the reinforcement layers of Reinforced Earth® wall and attached to the existing structure. The overlaps between reinforcements ensure their frictional connection on both sides of the structure. This solution has the advantage to keep the flexibility of the combined wall system but requires sufficient space for overlaps of the reinforcements.

Direct Link system

The reinforcements of the Reinforced Earth® wall are directly connected to the existing structure. This solution easily adapts to very narrow or limited space but requires further precautions in terms of construction.

Adaptation to existing structure

The existing structure or natural feature against which the Reinforced Earth® wall is constructed has its importance to the TerraLink® design, especially in determining the suitable technique for attachment of the reinforcements.

The existing structure could be a soil nail wall, Reinforced Earth® wall or other retaining wall, or an existing natural feature such as sloped terrain or bedrock. Whatever its origin, a specific assessment is required to ensure that the existing structure is safe enough or needs evaluation of the consolidated works to support the new load configuration.



North Tarrant Express near Dallas - Texas, USA

The main advantages are:

- Reduced footprint at the base of the structure
- Minimal disruption of the traffic flow during construction
- Speed of construction
- Saving demolition of the current structure
- Reduction of select backfill volume

Construction in steep topography context

Another main application is the construction of retaining walls in sloped terrain such as an existing embankment, cut slope or rocky outcrop. A standard retaining wall solution requires wide and expensive earthworks, including costly excavations. The use of TerraLink® system reduces the footprint compared to traditional solutions, and consequently the volume of excavated materials. The decrease of excavation and backfill material make this technique both sustainable and economical.

The main advantages are:

- Reduced footprint at the base of the structure
- Economy of excavation works
- Decrease of excavated materials (Economy of recovery/landfill or treatment)
- Speed of construction
- Reduction of technical backfilling
- Continuity of facing appearance with other adjacent full volume Reinforced Earth® walls



Kemerhisar - Pozanti motorway, Turkey

Field of application

The TerraLink® system is an excellent alternative when site constraints prevent the construction of traditional gravity retaining walls. Its field of applications depends on environmental, technical and economic considerations.

Widening of platform in urban environment

Due to the increase of traffic, providing a widened of platform is often necessary. In restricted urban areas the construction of new ramps is often just in front of existing ramps. A standard retaining wall would have the drawback to partially dismantle the current ramp in order to build the new one. The TerraLink® system enables the construction of the new ramp while keeping in place the existing wall, maintaining traffic use for most of the construction time.



N1 Gauteng Freeway widening - Johannesburg, South Africa



North Tarrant Express near Dallas - Texas, USA



Langeni, South Africa

This wealth of expertise has led Geoquest to develop processes offering common advantages:

- Reliable and sustainable materials
- Savings in terms of time and resources
- Capacity to adapt to complex situations
- Integration into the environment, in particular due to an extensive range of panel finishes

The Reinforced Earth® technique has revolutionized structural design and is applicable for all kinds of structures:

- Road
- Railway
- Marine and waterway
- Industrial and protective

The Reinforced Earth® technique, a major innovation

Recognized as **a major innovation in the field of civil engineering**, the Reinforced Earth® technique provides numerous structural solutions for owners and contractors ranging from retaining walls to bridge abutments.

As the world leader in mechanically stabilized earth, Geoquest has a presence in five continents, and benefits from both local and international expertise.



RN 116 - Créneaux du Pallat, France